

INDUSTRY SPECIFICATIONS BY PRODUCT (For use by sales/order entry personnel on customer inquiries)

Market Segment	BF-1000	HT-800 Series	HT-1200 Series	HT-1500
General Industrial	For UL 94 ratings See UL File E83967 for current information at UL.com and next page			
	ASTM D 1056 1A1	AMS-3195 (E)	AMS-3302 (G)	AMS-3320 (G)
		AMS-3196 (F)	AMS-3303 (J)	
			AMS-3304 (G)	
			A-A-59588	
Automotive	Chrysler MS-AY556 (A) Table 1	Chrysler MS-AY556 Table 1		
Aerospace	McDonnell Douglas DMS-1980 (F) Grade 1, Class 1	McDonnell Douglas DMS-1980 (F) Grade 3, Class 1		
	Airbus ABS 5006			
	Airbus AIMS 04-14-002 (Spec issue #3)			
	Boeing BMS 1-68 (H)			
Mass Transit	Alstom Engineering A00-497 (G)			
Other	FDA 21CFR 177.2600 (White color only)	FDA 21CFR 177.2600 (Gray color only)	FDA 21CFR177.2600 (HT-1250 Gray only)	AMS 3320, NOT on 1/32" material

Note: Meets the ingredients Requirements of FDA 21CFR 177.2600 For Food Contact section C.

The information contained in this Specification list is intended to assist you in designing with Rogers' High Performance Foam Materials. It is not intended to and does not create any warranties, express or implied, including any warranty of merchantability or fitness for a particular purpose or that the results shown on the Specification list will be achieved by a user for a particular purpose. The user should determine the suitability of Rogers' High Performance Foam Materials for each application. The Rogers logo, The world runs better with Rogers. and BISCO are licensed trademarks of Rogers Corporation. © 2003, 2006, 2008, 2009 Rogers Corporation, All rights reserved. Printed in U.S.A., 9076-1209-PDF, Publication #180-078

UL Specifications by Product

	Gasketing (JML U2)				Flammability (OMFZ2)	
	157 Std	UL-1570 -1572	UL-50	UL-508	UL 94HF-1	UL 94V-0
	Basic Standard for Gasket and Seals	Lighting Fixtures	Electrical Enclosures	Industrial Control Equipment	Horizontal Burn	20mm Vertical Burn
BF-1000, White					Thickness > 0.047"	Thickness > 0.105"
BF-1000, Gray					Thickness > 0.047"	Thickness > 0.068"
HT-800, Black/ Gray	x	x	x	x	Thickness > 0.028"	Thickness > 0.028"
HT-800, Red	x	x	x	x	Thickness > 0.028"	Thickness > 0.102"
BF-2000 (EP-2022), Black					Thickness > 0.087"	Thickness > 0.087"
HT-820, Black					Thickness > 0.028"	Thickness > 0.028"
HT-820, Gray	x	x	x	x	Thickness > 0.028"	Thickness > 0.028"
HT-840, Gray					Thickness > 0.028"	Thickness > 0.063"
HT-870, Black/Red	x	x	x	x	Thickness > 0.059"	Thickness > 0.059"

Note: Typical values are a representation of an average value for the population of the property. For specification values contact Rogers Corporation.

The information contained in this Specification list is intended to assist you in designing with Rogers' High Performance Foam Materials. It is not intended to and does not create any warranties, express or implied, including any warranty of merchantability or fitness for a particular purpose or that the results shown on the Specification list will be achieved by a user for a particular purpose. The user should determine the suitability of Rogers' High Performance Foam Materials for each application. The Rogers logo, The world runs better with Rogers. and BISCO are licensed trademarks of Rogers Corporation. © 2003, 2006, 2008, 2009 Rogers Corporation, All rights reserved. Printed in U.S.A., 9076-1209-PDF, Publication #180-078