

# BISCO® HT-800

BISCO® HT-800 medium firm silicone foam embodies the transition in the BISCO Silicone Cellular series from soft and conformable to firm and durable. It simultaneously retains the lightness of a foam while exhibiting enhanced sealing capabilities of a traditional sponge rubber.

## Features & Benefits, applicable to all BISCO® Cellular Materials (Foams):

- Patented chemistry and cell structure provide long term performance advantage
- Temperature independency
- UV/ Ozone resistant
- Rated to most stringent flame standards

PROPERTY	TEST METHOD	TYPICAL VALUE	SPECIFICATION
<b>PHYSICAL</b>			
Color	Visual	Black, Gray, Red	---
Thickness, mm (inches)	Internal	0.79 - 12.70 (0.031 - 0.500)	---
Density, kg/m <sup>3</sup> (lb./ft <sup>2</sup> )	Internal	352 (22)	300 - 473 (18.7 - 29.5)
Compression Force Deflection, kPa (psi)	ASTM D1056 25% Deflection	67 (9.7)	41 - 97 (6 - 14)
Tensile Strength, kPa (psi)	ASTM D412	---	240 (35)
Elongation, % min	ASTM D412	---	45
Compression Set, %	ASTM D1056 100°C (212°F), 22 hrs @ 50%	2.4	< 5

PROPERTY	TEST METHOD	TYPICAL VALUE	SPECIFICATION
<b>FLAMMABILITY PROPERTIES</b>			
Flame Resistance	UL 94 (File E83967) V-0 ; HF-1	---	Meets
Flame Spread Index (Is)	ASTM E162 Flaming Mode < 35	---	Meets
Smoke Density (Ds)	ASTM E662 Flaming Mode @ 1.5 min, < 100 Flaming Mode @ 4.0 min, < 200	---	Meets
Burn Length	FMVSS 302 < 100 mm/min	---	Meets

PROPERTY	TEST METHOD	TYPICAL VALUE	SPECIFICATION
<b>THERMAL PROPERTIES</b>			
Temperature Range, °C (°F)	Internal	---	-55 to +200 (-67 to +392)
Thermal Conductivity, W/m °K	ASTM D518	---	0.076
Low Temperature Flex	ASTM D1056 -55°C (-67°F)	---	Pass
Low Temperature Brittleness	ASTM D746 -55°C (-67°F)	---	Pass

#### Standard Thickness Tolerances

NOMINAL THICKNESS	TOLERANCE
mm (inches)	mm (inches)
0.79 (0.031)	+ 0.381/0.102 (+ 0.015/-0.004)
1.60 (0.063)	± 0.058 (± 0.020)
2.39 (0.094)	± 0.058 (± 0.020)
3.18 (0.125)	± 0.635 (± 0.025)
4.78 (0.188)	± 0.635 (± 0.025)
6.35 (0.250)	± 0.762 (± 0.030)
9.53 (0.375)	± 1.143 (± 0.045)
12.70 (0.500)	± 1.270 (± 0.050)

#### Slit Material and Tape (PSA) Width Tolerances

NOMINAL WIDTH	TOLERANCE
mm (inches)	mm (inches)
> 0 - 76 (> 0 - 3)	± 1.60 (± 0.063)
> 76 - 203 (> 3 - 8)	± 2.39 (± 0.094)
> 203 - 305 (> 8 - 12)	± 3.18 (± 0.125)
> 305 - 457 (> 12 - 18)	± 4.78 (± 0.188)
> 457 - 660 (> 18 - 26)	± 5.56 (± 0.219)
> 660 - 914 (> 26 - 36)	+ 25.4/- 0 (+ 1/- 0)

#### VALUE ADDED OFFERINGS

- Adhesive (PSA) lamination
- Slit material/tapes

#### Notes:

- All metric conversions are approximate. Reference US customary units for official values and tolerances.
- Additional technical information is available.
- Values should not be used for specification limits.